

CE Declaration of Performance (DoP)

N° MP0060029

In accordance with annex III of the EU regulation 305/2011

1. Unique identification code of the product-type:

PARACRYL PARQUET

2. Type, batch or serial number, or any other element allowing identification of the construction product as required pursuant to Article 11 (4):

Batch number: See entry on packaging

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Sealant for facade application interior – Conform EN 15651-1:2012 Type F INT

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 (5):

**DL CHEMICALS
Roterijstraat 201-203
B 8793 Waregem**

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 4
System 3**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

The determination of the product type based on type testing under system 4 is the sole responsibility of the manufacturer.

The notified body *EFFECTIS*, identification number *NB 1234*, performed the determination of the class as regards the reaction to fire, under system 3 and issued : a test report

8. In case of the declaration of performance concerning a construction product of which a European Technical Assessment has been issued:

Not applicable

CE Declaration of Performance (DoP)

N° MP0060029

In accordance with annex III of the EU regulation 305/2011

9. Declared Performances:

| Essential characteristics – Type F INT | Performance | Technical harmonised specification |
|--|-------------|------------------------------------|
| Reaction to fire (classification according EN 13501-1:2007) | Class E | EN 15651-1:2012 |
| Release of chemicals dangerous to the environment and health | NPD | |
| Water and air tightness | | |
| Resistance to flow (according EN ISO 7390) | ≤ 5 mm | |
| Loss of volume (according EN ISO 10563) | ≤ 45% | |
| Tensile properties – elongation at break – according ISO 8339 | ≥ 25% | |
| Durability | Pass | |
| Conditioning : Method A Substrate : Façade : Anodized Aluminium + M2 Concrete | | |

10. The performance of the product identified in points 1 & 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified under point 4.

Signed for and on behalf of the manufacturer by



Joris Van Hoey
 Quality Control Manager

Waregem – September 2022

CE marking

N° MP0060029

In accordance with annex III of the EU regulation 305/2011



14

DL CHEMICALS

Roterijstraat 201-203 B-8793 Waregem, België

PARACRYL PARQUET

DoP No. MP0060029

EN 15651-1:2012

Notified Body 1234

Sealant for facade application interior – Type F INT

| Essential characteristics | Performance | Technical harmonised specification |
|--|-------------|------------------------------------|
| Reaction to fire | Class E | EN 15651-1:2012 |
| Release of chemicals dangerous to the environment and health | NPD | |
| Water and air tightness | | |
| Resistance to flow | ≤ 5 mm | |
| Loss of volume | ≤ 45% | |
| • Tensile properties – elongation at break | ≥ 25% | |
| Durability | Pass | |
| Conditioning: Method A Substrate Façade: Anodized Aluminium + M2 Concrete | | |
| https://www.dl-chem.com/nl/dop | | |

UKCA Declaration of Performance (DoP)

N° MP0060029

In accordance with annex III of the EU regulation 305/2011

1. Unique identification code of the product-type:

PARACRYL PARQUET

2. Type, batch or serial number, or any other element allowing identification of the construction product as required pursuant to Article 11 (4):

Batch number: See entry on packaging

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Sealant for facade application interior – Conform EN 15651-1:2012 Type F INT

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 (5):

**DL CHEMICALS
Roterijstraat 201-203
B 8793 Waregem**

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 4
System 3**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

The determination of the product type based on type testing under system 4 is the sole responsibility of the manufacturer.

The approved body *EFFECTIS*, identification number *AB 1234*, performed the determination of the class as regards the reaction to fire, under system 3 and issued : a test report

8. In case of the declaration of performance concerning a construction product of which a European Technical Assessment has been issued:

Not applicable

UKCA Declaration of Performance (DoP)

N° MP0060029

In accordance with annex III of the EU regulation 305/2011

9. Declared Performances:

| Essential characteristics – Type F INT | Performance | Technical designated specification |
|--|-------------|------------------------------------|
| Reaction to fire (classification according EN 13501-1:2007) | Class E | EN 15651-1:2012 |
| Release of chemicals dangerous to the environment and health | NPD | |
| Water and air tightness | | |
| Resistance to flow (according EN ISO 7390) | ≤ 5 mm | |
| Loss of volume (according EN ISO 10563) | ≤ 45% | |
| Tensile properties – elongation at break – according ISO 8339 | ≥ 25% | |
| Durability | Pass | |
| Conditioning : Method A Substrate : Façade : Anodized Aluminium + M2 Concrete | | |

10. The performance of the product identified in points 1 & 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified under point 4.

Signed for and on behalf of the manufacturer by



Joris Van Hoey
 Quality Control Manager

Waregem – September 2022

UKCA marking

N° MP0060029

In accordance with annex III of the EU regulation 305/2011

**UK
CA**

22

DL CHEMICALS
 Roterijstraat 201-203 B-8793 Waregem, België

PARACRYL PARQUET

DoP No. MP0060029

EN 15651-1:2012

Approved Body 1234

Sealant for facade application interior – Type F INT

| Essential characteristics | Performance | Technical designated specification |
|--|-------------|------------------------------------|
| Reaction to fire | Class E | EN 15651-1:2012 |
| Release of chemicals dangerous to the environment and health | NPD | |
| Water and air tightness | | |
| Resistance to flow | ≤ 5 mm | |
| Loss of volume | ≤ 45% | |
| Tensile properties – elongation at break | ≥ 25% | |
| Durability | Pass | |
| Conditioning: Method A Substrate Façade: Anodized Aluminium + M2 Concrete | | |
| https://www.dl-chem.com/nl/dop | | |