


**CHARACTERISTICS**

- Flexible butyl and polyisobutylen based cordon sealant
- With protection foil
- Available in round profiles

**APPLICATIONS**

- Is used for temporarily and permanent jointing in building and manufacturing industry
- For connections between ceiling plates, waterproof connections between corrugated sheets, etc.

**TECHNICAL CHARACTERISTICS**

Colour	Grey
Basis	Butyl and polyisobutylene
Density	1,85 g/cm <sup>3</sup>
Processing temperature	+5°C - +40°C
Shelf life, in the original packing in dry conditions between +5°C - +25°C	24 months
Plasticity	35 <P> 120
Fluidity at 23°C and at 70°C	0 mm
Solid contents	100%
Temperature resistance	-50°C - +80°C
Water vapour permeability	Impermeable
Resistance	To water and salt water: excellent To detergents: very good To diluted acids: good To diluted alkalines: very good To alcohol: medium To organic solvents: bad

**PACKING AND MEASUREMENTS**

Diameter	Packing	Pallet
Ø 6 mm	22 rolls of 8 m/box	30 boxes/pallet
Ø 9,5 mm	16 rolls of 6 m/box	30 boxes/pallet
Ø 13 mm	16 rolls of 4 m/box	24 boxes/pallet

**METHOD OF USE**
**Preparation**

All surfaces should be dry and clean, and free from grease. The user must check whether the product is suitable for its application. When in doubt, contact our technical support service.

**Application**

- Cut **Paraform 20** at desired length. Apply the protection foil and the band on the surfaces. Press firmly from the inside towards the outside to avoid air bubbles.
- Remove the protection foil and press the parts firmly together. The parts stick immediately. After one hour the adhesion strength is optimal.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply.