WOODEN PACKERS

CHARACTERISTICS

- All our wooden packers are conform to the relative norms.
- They are colourfast and treated with products that correspond to the STS 38.
- The thickness of the wooden packers is shown by the colour
- Beech is one of the strongest kinds of wood in these parts of the country.
 - AQUA BEITS: This is a colouring that has been made from natural materials. In addition to that, there have been added products that stop rotting (STS 38). With this treatment the wooden packers are resistant to water and colourfast.

| TECHNICAL CHARACTERISTICS | |
|----------------------------|--|
| Kind of wood | Beech |
| Grain | Fine |
| Thread | Straight and regular |
| Colour | Cream-yellow, lightly brown or reddish |
| Mass volume (source T.N.O) | 710 kg/m³ dry |
| Modulus of elasticity | E = 12300 N/mm ² |
| Bending strength | 113 N/mm ² |
| Compression strength | 54 N/mm ² |
| Shearing strength | 10 N/mm ² |

DIMENSIONS AND COLOURS

+/- 100 pieces/bag. These small bags are packed in cartons or bags. The quantity depends on the size.

The width varies from 12 mm to 30 mm and passes constantly with 2 mm. Standard sizes: 12-20-22-24-26-28-30, other widths are available on demand.

Colour code

Thickness 1 mm = nature Thickness 2 mm = red Thickness 3 mm = green Thickness 4 mm = yellow Thickness 5 mm = blue Thickness 6 mm = black

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply.



DL Chemicals nv Roterijstraat 201-203 - Zone 5 Snepbeek - 8793 Waregem - Belgium T +32 56 62 70 51 - F +32 56 60 95 68 info@dl-chem.com - www.dl-chem.com