

CE Declaration of Performance (DoP)

N° MP0240003

In accordance with annex III of the EU regulation 305/2011

1. Unique identification code of the product-type:

Paracol PVC PVC

2. Type, batch or serial number, or any other element allowing identification of the construction product as required pursuant to Article 11 (4):

Batch number: See entry on packaging

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**Adhesive for PVC-U piping systems for liquids not under pressure – In accordance with EN 14680:2006
For use in installations for the transport, disposal and storage of water, not intended for human consumption**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 (5):

**DL CHEMICALS
Roterijstraat 201-203
B-8793 Waregem**

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

EN 14680:2006

8. In case of the declaration of performance concerning a construction product of which a European Technical Assessment has been issued:

Not applicable

CE Declaration of Performance (DoP)

N° MP0240003

In accordance with annex III of the EU regulation 305/2011

9. Declared Performances:

Essential characteristics	Performance	Technical harmonised specification
<i>Shear strength :</i> - after 1 hour drying time - after 24 hours drying time - after 480 hours drying time	$\geq 0.25 \text{ MPa}$ $\geq 1.5 \text{ MPa}$ $\geq 3.0 \text{ MPa}$	<i>EN 14680:2006</i>
<i>Leak tightness</i>	<i>No leakage</i>	
<i>Resistant to elevated temperature (cyclic test)</i>	<i>No leakage</i>	
<i>Durability on leak tightness and temperature resistance</i>	<i>No leakage</i>	

10. The performance of the product identified in points 1 & 2 is in conformity with the declared performance in point 9 .
 This declaration of performance is issued under the sole responsibility of the manufacturer identified under point 4.

Signed for and on behalf of the manufacturer by



Joris Van Hoey
 Quality Control Manager

Waregem – September 2022

CE marking

N° MP0240003

In accordance with annex III of the EU regulation 305/2011



14

DL CHEMICALS

Roterijstraat 201-203 B-8793 Waregem, België

Paracol PVC PVC

DoP No. MP0240003

EN 14680:2006

Adhesive for PVC-U piping systems for liquids not under pressure – In accordance with EN 14680:2006
For use in installations for the transport, disposal and storage of water, not intended for human consumption

Essential characteristics	Performance	Technical harmonised specification
Shear strength : - after 1 hour drying time - after 24 hours drying time - after 480 hours drying time	≥ 0.25 MPa ≥ 1.5 MPa ≥ 3.0 MPa	EN 14680:2006
Leak tightness	No leakage	
Resistant to elevated temperature (cyclic test)	No leakage	
https://www.dl-chem.com/nl/dop		

UKCA Declaration of Performance (DoP)

N° MP0240003

In accordance with annex III of the EU regulation 305/2011

1. Unique identification code of the product-type:

Paracol PVC PVC

2. Type, batch or serial number, or any other element allowing identification of the construction product as required pursuant to Article 11 (4):

Batch number: See entry on packaging

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**Adhesive for PVC-U piping systems for liquids not under pressure – In accordance with EN 14680:2006
For use in installations for the transport, disposal and storage of water, not intended for human consumption**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 (5):

**DL CHEMICALS
Roterijstraat 201-203
B-8793 Waregem**

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

EN 14680:2006

8. In case of the declaration of performance concerning a construction product of which a European Technical Assessment has been issued:

Not applicable

UKCA Declaration of Performance (DoP)

N° MP0240003

In accordance with annex III of the EU regulation 305/2011

9. Declared Performances:

Essential characteristics	Performance	Technical designated specification
<i>Shear strength :</i> - after 1 hour drying time - after 24 hours drying time - after 480 hours drying time	$\geq 0.25 \text{ MPa}$ $\geq 1.5 \text{ MPa}$ $\geq 3.0 \text{ MPa}$	EN 14680:2006
<i>Leak tightness</i>	<i>No leakage</i>	
<i>Resistant to elevated temperature (cyclic test)</i>	<i>No leakage</i>	
<i>Durability on leak tightness and temperature resistance</i>	<i>No leakage</i>	

10. The performance of the product identified in points 1 & 2 is in conformity with the declared performance in point 9 .
This declaration of performance is issued under the sole responsibility of the manufacturer identified under point 4.

Signed for and on behalf of the manufacturer by



Joris Van Hoey
Quality Control Manager

Waregem – September 2022

UKCA marking

N° MP0240003

In accordance with annex III of the EU regulation 305/2011

UK CA

14

DL CHEMICALS

Roterijstraat 201-203 B-8793 Waregem, België

Paracol PVC PVC

DoP No. MP0240003

EN 14680:2006

Adhesive for PVC-U piping systems for liquids not under pressure – In accordance with EN 14680:2006
For use in installations for the transport, disposal and storage of water, not intended for human consumption

Essential characteristics	Performance	Technical designated specification
Shear strength : - after 1 hour drying time - after 24 hours drying time - after 480 hours drying time	≥ 0.25 MPa ≥ 1.5 MPa ≥ 3.0 MPa	EN 14680:2006
Leak tightness	No leakage	
Resistant to elevated temperature (cyclic test)	No leakage	
https://www.dl-chem.com/nl/dop		