



## CHARACTERISTICS

- Protection spray
- Remains supple
- Prevents corrosion
- Weather resistant
- Excellent adhesion
- Sound-insulating
- Resistant to weak acids and bases

## APPLICATIONS

- Protection product for wood: wooden windows, wooden poles...
- Protection for the down side of vehicles.
- Waterproofing all kinds of surfaces.

TECHNICAL CHARACTERISTICS	
VOC content	+/- 70% w/w
Drying time	Dust dry after +/- 60 minutes*
Processing temperature	15°C - 25°C
Shelf life, in the original packing in dry and cool conditions	10 years

(\*) The drying time depends on the ambient temperature, the humidity and the applied layer thickness.

PACKING AND COLOURS
6 spray cans of 400 ml/box
Black

## METHOD OF USE

### Preparation

Cover the surrounding materials. The surface must be clean, dry and free of grease. Remove loose old paint residues and rust and then sand.

### Application

- Shake the spray can during 2 minutes and spray a test piece before use.
- Spray at a distance of 25 - 30 cm. Apply in different layers.
- After use, spray the valve clean (hold the spray can upside down and keep the spray nozzle pressed for 5 seconds).

## SAFETY

Safety data sheet available on request.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply.