ALU CLEANER SOFT

CHARACTERISTICS

- Cleansing product
- High cleaning capacity
- Does not attack lacquers
- Solvent based

APPLICATIONS

- For removing dirt and grease on all lacquered and unlacquered metals.
- Can be used to remove the following dirt: asphalt marks, grease marks and all persistent dirt

| TECHNICAL CHARACTERISTICS | |
|--|----------------|
| Physical state (20°C) | Liquid |
| Colour | Transparent |
| Odour | Characteristic |
| Boiling point / interval | 83°C |
| Flash point | 12°C |
| Density (20°C) | 0,79 g/cc |
| Shelf life, in the original packing in dry conditions between $+5^{\circ}\text{C} - +25^{\circ}\text{C}$ | 2 years |

| PACKING |
|---|
| 15 cans of 500 ml/box - 48 boxes/pallet |
| Can 5 I - 120 cans/pallet |
| Jar 25 I - 26 jars/pallet |

METHOD OF USE

Application

- Remove dirt and scratches
- Polish with a clean and dry cloth

SAFETY

Safety data sheet available on request.

LIMITATIONS

- Not appropriate for rust spots
- On relief lacquers we recommend Alu Cleaner Structure

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply.



Rev. 2, 01/09/16

