

**CHARACTERISTICS**

- Self-adhesive foam tape in PVC
- Semi-closed cells
- Waterproof from 30% compression
- One-sided self-adhesive
- UV resistant

APPLICATIONS

- Can be used as backfilling.
- For joint sealing between wall and frame.
- Sealing between partition wall and floor or wall.

TECHNICAL CHARACTERISTICS

Colour	Dark grey
Density	100 - 125 kg/m ³
Tensile strength DIN 53571	≥ 0,15 N/mm ²
Elongation at break DIN 53571	≥ 120%
Tear resistance DIN 53515	≥ 0,80 N/mm
Pressure deformation residue DIN 53572	≤ 45%
Water density	≥ 30% compression
Water absorption	≤ 30%
Temperature resistance	-30°C - +60°C
Shore 00 hardness	20 - 40
Resistance to	Obsolescence : Very good Steam : Good Acids : Good Mineral oils : Good Alcohol : Good Alkaline liquids : Good Water : Good Petrol : Average Acids and strong alkaline liquids : Average

PACKING AND MEASUREMENTS

Width x thickness	Packing
9 x 10 mm	6 rolls of 75 m/box
15 x 10 mm	6 rolls of 50 m/box
15 x 15 mm	6 rolls of 35 m/box

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply.