



CHARACTERISTICS

- Water-based primer
- Highly improved adherence
- In order to obtain an ideal adherence of the parquet adhesive and dispersion adhesive for flexible floor coverings
- Also reinforces floor surfaces on a concrete base
- Easy to use
- Fast drying
- Solvent free (odour free)

APPLICATIONS

- Can be used on absorbent substrates and tiled floors.
- Suitable as an adhesion primer for underfloor heating, when screed is dry.

TECHNICAL CHARACTERISTICS	
Colour	White (dries transparent)
Basis	Acrylic dispersion
Curing system	Physical drying
Density	+/- 1.02 g/ml
Processing temperature	+15°C up to +25°C
Consumption	100 - 200 ml/m ² (5 - 10 m ² /liter)
Drying time	2 h - 24 h, depending on the circumstances
Shelf life, in the original closed packing in a dry, cool place free of frost.	12 months

PACKING
Jar of 5 l - 120 jars/pallet

METHOD OF USE

Application

- Shake the product before use.
- Apply the primer in one layer with a roll or a brush.
- The primer must be completely dry before you apply the parquet adhesive. Dry time is between 2 h and 24 h, depending on the circumstances. The primer cures by evaporation of water.

Cleaning

With water

SAFETY

Safety data sheet available online: www.dl-chem.com.

LIMITATIONS

- Not suitable for subfloors with residual moisture or rising damp.
- Not suitable as a moisture barrier.
- Not suitable for outdoor use.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply.