



## CHARACTERISTICS

- Lubricant
- On the basis of a high-quality, translucent silicone
- Due to the absence of colour and metal parts, this is the ideal product for smoothing

## APPLICATIONS

- Anti-corrosion for different materials.
- Damp-resistance.
- Smoothing of each sensitive mechanism.
- Preventing rubbers to dry out.
- Glow on plastic and vinyl.

## TECHNICAL CHARACTERISTICS

Components	Silicone-oil, aliphatic solvent, hydrocarbon-propellant
Colour	Colourless liquid
Density	0,76 g/cm <sup>3</sup>
Solids content	20%
pH	Without
Ignition point	< 0°C
Brightness of the silicone	99,9%
Processing temperature	-40°C - +240°C
Shelf life, in the original packing in dry conditions between +5°C - +25°C	4 years

## PACKING

6 spray cans of 600 ml/box - 87 boxes/pallet

## METHOD OF USE

### Application

- Dirt and other traces should be avoided.
- Shake the can well.
- Spraying is done by short pushing on the compounds to be protected.
- Let penetrate the product by manipulating the lubricated parts.

## SAFETY

Safety data sheet available on request.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply.