

CE Declaration of Performance (DoP)

N° MP0070001

In accordance with annex III of the EU regulation 305/2011

1. Unique identification code of the product-type:

PARABOND CONSTRUCTION

2. Type, batch or serial number, or any other element allowing identification of the construction product as required pursuant to Article 11 (4):

Batch number: See entry on packaging

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Sealant for facade application interior and exterior – Conform EN 15651-1:2012 Type F EXT-INT Class 25 HM

Sealant for pedestrian walkways – Conform EN 15651-4:2012 Type PW Class 25 HM

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 (5):

**DL CHEMICALS
Roterijstraat 201-203
B 8793 Waregem**

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

**The notified body *GINGER CEBTP*, identification number *NB 0074*,
performed the determination of the product type based on type
testing under system 3 and issued: a test report**

**The notified body *EFFECTIS*, identification number *NB 1234*,
performed the determination of the class as regards the reaction
to fire, under system 3 and issued: a test report**

8. In case of the declaration of performance concerning a construction product of which a European Technical Assessment has been issued:

Not applicable

CE Declaration of Performance (DoP)

N° MP0070001

In accordance with annex III of the EU regulation 305/2011

9. Declared Performances:

| Essential characteristics – Type F EXT-INT | Performance | Technical harmonised specification |
|--|-------------|------------------------------------|
| Reaction to fire (classification according EN 13501-1:2007) | Class E | EN 15651-1:2012 |
| Release of chemicals dangerous to the environment and health | NPD | |
| Water and air tightness | | |
| Resistance to flow (according EN ISO 7390) | ≤ 3 mm | |
| Loss of volume (according EN ISO 10563) | ≤ 10% | |
| Tensile properties • at maintained extension after water immersion (according EN ISO 10590) | Pass | |
| Durability | Pass | |
| Conditioning : Method A Substrate : Façade : Anodized Aluminium + M2 Concrete with primer DL 2001 | | |

| Essential characteristics – Type PW | Performance | Technical harmonised specification |
|--|-------------|------------------------------------|
| Reaction to fire (classification according EN 13501-1:2007) | Class E | EN 15651-4:2012 |
| Release of chemicals dangerous to the environment and health | NPD | |
| Water and air tightness | | |
| Tensile properties at maintained extension (according EN ISO 8340) | Pass | |
| Tear resistance – modulus at break - (according EN ISO 8339) | Pass | |
| Adhesion-cohesion properties at maintained extension after 28 days salt water immersion (according EN ISO 10590) | Pass | |
| Durability | Pass | |
| Conditioning : Method A Substrate : Façade : Anodized Aluminium + M2 Concrete with primer DL 2001 | | |

10. The performance of the product identified in points 1 & 2 is in conformity with the declared performance in point 9.
 This declaration of performance is issued under the sole responsibility of the manufacturer identified under point 4.

Signed for and on behalf of the manufacturer by:



Joris Van Hoey
 Quality Control Manager

Waregem – September 2022

CE marking

N° MP0070001

In accordance with annex III of the EU regulation 305/2011



22

DL CHEMICALS

Roterijstraat 201-203 B-8793 Waregem, België

PARABOND CONSTRUCTION

DoP No. MP0070001

EN 15651-1:2012

EN 15651-4:2012

Notified Body 0074

Notified Body 1234

Sealant for facade application interior and exterior – Type F EXT-INT Class 25 HM

Sealant for pedestrian walkways – Type PW Class 25 HM

| Essential characteristics | Performance | Technical harmonised specification |
|--|-------------|------------------------------------|
| Reaction to fire | Class E | EN 15651-1:2012 EN 15651-4:2012 |
| Release of chemicals dangerous to the environment and health | NPD | |
| Water and air tightness | | |
| Resistance to flow | ≤ 3 mm | |
| Loss of volume | ≤ 10% | |
| Tensile properties <ul style="list-style-type: none">at maintained extension after water immersion | Pass | |
| Tensile properties at maintained extension | Pass | |
| Tear resistance – modulus at break | Pass | |
| Adhesion-cohesion properties at maintained extension after 28 days salt water immersion | Pass | |
| Durability | Pass | |
| Conditioning: Method A Substrate Façade: Anodized Aluminium + M2 Concrete with primer DL 2001 | | |
| https://www.dl-chem.com/en/dop | | |

UKCA Declaration of Performance (DoP)

N° MP0070001

In accordance with annex III of the EU regulation 305/2011

1. Unique identification code of the product-type:

PARABOND CONSTRUCTION

2. Type, batch or serial number, or any other element allowing identification of the construction product as required pursuant to Article 11 (4):

Batch number: See entry on packaging

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Sealant for facade application interior and exterior – Conform EN 15651-1:2012 Type F EXT-INT Class 25 HM

Sealant for pedestrian walkways – Conform EN 15651-4:2012 Type PW Class 25 HM

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 (5):

**DL CHEMICALS
Roterijstraat 201-203
B 8793 Waregem**

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

The approved body *4Ward Testing*, identification number *AB 2538*, performed the determination of the product type based on type testing under system 3 and issued: a test report

The approved body *EFFECTIS*, identification number *AB 1234*, performed the determination of the class as regards the reaction to fire, under system 3 and issued: a test report

8. In case of the declaration of performance concerning a construction product of which a European Technical Assessment has been issued:

Not applicable

UKCA Declaration of Performance (DoP)

N° MP0070001

In accordance with annex III of the EU regulation 305/2011

9. Declared Performances:

| Essential characteristics – Type F EXT-INT | Performance | Technical designated specification |
|--|-------------|------------------------------------|
| Reaction to fire (classification according EN 13501-1:2007) | Class E | BS EN 15651-1:2012 |
| Release of chemicals dangerous to the environment and health | NPD | |
| Water and air tightness | | |
| Resistance to flow (according BS EN ISO 7390) | ≤ 3 mm | |
| Loss of volume (according BS EN ISO 10563) | ≤ 10% | |
| Tensile properties • at maintained extension after water immersion (according BS EN ISO 10590) | Pass | |
| Durability | Pass | |
| Conditioning : Method A Substrate : Façade : Anodized Aluminium + M2 Concrete with primer DL 2001 | | |

| Essential characteristics – Type PW | Performance | Technical designated specification |
|---|-------------|------------------------------------|
| Reaction to fire (classification according EN 13501-1:2007) | Class E | BS EN 15651-4:2012 |
| Release of chemicals dangerous to the environment and health | NPD | |
| Water and air tightness | | |
| Tensile properties at maintained extension (according BS EN ISO 8340) | Pass | |
| Tear resistance – modulus at break - (according BS EN ISO 8339) | Pass | |
| Adhesion-cohesion properties at maintained extension after 28 days salt water immersion (according BS EN ISO 10590) | Pass | |
| Durability | Pass | |
| Conditioning : Method A Substrate : Façade : Anodized Aluminium + M2 Concrete with primer DL 2001 | | |

10. The performance of the product identified in points 1 & 2 is in conformity with the declared performance in point 9.
 This declaration of performance is issued under the sole responsibility of the manufacturer identified under point 4.

Signed for and on behalf of the manufacturer by:



Joris Van Hoey
 Quality Control Manager

Waregem – September 2022

UKCA marking

N° MP0070001

In accordance with annex III of the EU regulation 305/2011

UK CA

22

DL CHEMICALS

Roterijstraat 201-203 B-8793 Waregem, België

PARABOND CONSTRUCTION

DoP No. MP0070001

EN 15651-1:2012

EN 15651-4:2012

Approved Body 2538

Approved Body 1234

Sealant for facade application interior and exterior – Type F EXT-INT Class 25 HM

Sealant for pedestrian walkways – Type PW Class 25 HM

| Essential characteristics | Performance | Technical designated specification |
|--|-------------|--|
| Reaction to fire | Class E | BS EN 15651-1:2012 BS EN 15651-4:2012 |
| Release of chemicals dangerous to the environment and health | NPD | |
| Water and air tightness | | |
| Resistance to flow | ≤ 3 mm | |
| Loss of volume | ≤ 10% | |
| Tensile properties <ul style="list-style-type: none">at maintained extension after water immersion | Pass | |
| Tensile properties at maintained extension | Pass | |
| Tear resistance – modulus at break | Pass | |
| Adhesion-cohesion properties at maintained extension after 28 days salt water immersion | Pass | |
| Durability | Pass | |
| Conditioning: Method A Substrate Façade: Anodized Aluminium + M2 Concrete with primer DL 2001 | | |
| https://www.dl-chem.com/en/dop | | |