



CHARACTERISTICS

- Packers of solid synthetic
- Long service life
- Grains at both sides in order to avoid the packers from sliding
- Hardness shore D : 61, Hardness shore A : 95
- Length of 80 mm
- The packers NDR are available in 5 thicknesses in widths from 20 to 48 mm: 1 mm = black, 2 mm = red, 3 mm = green, 4 mm = yellow, 5 mm = blue

APPLICATIONS

- For insulating glazing. The packers are compatible with all sealants intended for the manufacture of insulating glazing.
- When using ordinary packers, glass can deform the packers. This is avoided when using these hard plastic packers.

TECHNICAL CHARACTERISTICS

Shelf life of unopened product	240 months
--------------------------------	------------

PACKING AND COLOURS

20 x 1 mm : box 1000pcs - 40 pieces/pallet
20 x 2 mm : box 1000pcs - 40 pieces/pallet
20 x 3 mm : box 1000pcs - 40 pieces/pallet
20 x 4 mm : box 1000pcs - 40 pieces/pallet
20 x 5 mm : box 1000pcs - 40 pieces/pallet
22 x 1 mm : box 1000pcs - 40 pieces/pallet
22 x 2 mm : box 1000pcs - 60 pieces/pallet
22 x 3 mm : box 1000pcs - 40 pieces/pallet
22 x 4 mm : box 1000pcs - 40 pieces/pallet
22 x 5 mm : box 1000pcs - 40 pieces/pallet
24 x 1 mm : box 1000pcs - 40 pieces/pallet
24 x 2 mm : box 1000pcs - 40 pieces/pallet
24 x 3 mm : box 1000pcs - 40 pieces/pallet
24 x 4 mm : box 1000pcs - 40 pieces/pallet
24 x 5 mm : box 1000pcs - 40 pieces/pallet
26 x 1 mm : box 1000pcs - 40 pieces/pallet
26 x 2 mm : box 1000pcs - 60 pieces/pallet
26 x 3 mm : box 1000pcs - 40 pieces/pallet
26 x 4 mm : box 1000pcs - 40 pieces/pallet
26 x 5 mm : box 1000pcs - 40 pieces/pallet
28 x 1 mm : box 1000pcs - 40 pieces/pallet
28 x 2 mm : box 1000pcs - 40 pieces/pallet
28 x 3 mm : box 1000pcs - 60 pieces/pallet
28 x 4 mm : box 1000pcs - 60 pieces/pallet
28 x 5 mm : box 1000pcs - 60 pieces/pallet
30 x 1 mm : box 1000pcs - 40 pieces/pallet

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply

30 x 2 mm : box 1000pcs - 40 pieces/pallet
30 x 3 mm : box 1000pcs - 60 pieces/pallet
30 x 4 mm : box 1000pcs - 60 pieces/pallet
30 x 5 mm : box 1000pcs - 60 pieces/pallet
34 x 1 mm : box 1000pcs - 40 pieces/pallet
34 x 2 mm : box 1000pcs - 40 pieces/pallet
34 x 3 mm : box 1000pcs - 40 pieces/pallet
34 x 4 mm : box 1000pcs - 40 pieces/pallet
34 x 5 mm : box 1000pcs - 40 pieces/pallet
44 x 1 mm : box 1000pcs - 40 pieces/pallet
44 x 2 mm : box 1000pcs - 40 pieces/pallet
44 x 3 mm : box 1000pcs - 40 pieces/pallet
44 x 4 mm : box 1000pcs - 40 pieces/pallet
44 x 5 mm : box 1000pcs - 40 pieces/pallet
46 x 1 mm : box 1000pcs - 40 pieces/pallet
46 x 2 mm : box 1000pcs - 40 pieces/pallet
46 x 3 mm : box 1000pcs - 40 pieces/pallet
46 x 5 mm : box 1000pcs - 40 pieces/pallet
48 x 1 mm : box 1000pcs - 40 pieces/pallet
48 x 2 mm : box 1000pcs - 40 pieces/pallet
48 x 3 mm : box 1000pcs - 40 pieces/pallet
48 x 4 mm : box 1000pcs - 40 pieces/pallet
48 x 5 mm : box 1000pcs - 40 pieces/pallet
48 x 6 mm : box 1000pcs - 40 pieces/pallet

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply