

**CHARACTERISTICS**

- Plasticizer-free
- Highly resistant to aging
- One-sided self-adhesive
- Compatible with silicone, thiokol or other jointing compounds
- Resistant to salt water, chemicals, soap and detergents
- Closed cells

APPLICATIONS

- Suitable for aluminium, PVC and wood frames

TECHNICAL CHARACTERISTICS

Density: DIN 53420 (g/cm ³)	0.033
Compression strength: DIN 53577	30%: 0,05 N/mm ² 50%: 0,12 N/mm ² 70%: 0,25 N/mm ²
Water vapour permeability at 2 mm thickness: DIN 53122 (per 24h)	1.8 g/m ²
Water absorption	Na 7 dagen: 0,7%, na 28 dagen: 0,8% (DIN 53428)
Temperature resistance	-80°C - +100°C
Shelf life of unopened product	12 months

PACKING AND COLOURS

Grey
9 x 2 mm : 26 x roll 5X 20M/box - 650 pieces/pallet
9 x 3 mm : 20 x roll 5X 20M/box - 500 pieces/pallet
9 x 4 mm : 16 x roll 5X 20M/box - 400 pieces/pallet
9 x 5 mm : 22 x roll 5X 10M/box - 550 pieces/pallet
15 x 2 mm : 12 x roll 5X 20M/box - 600 pieces/pallet
15 x 3 mm : 12 x roll 5X 20M/box - 300 pieces/pallet
20 x 3 mm : 68 x roll 30M/box - 1700 pieces/pallet
20 x 3 mm : 8 x roll 5X 30M/box - 400 pieces/pallet
30 x 5 mm : 32 x roll 10M/box - 800 pieces/pallet
40 x 3 mm : 34 x roll 30M/box - 374 pieces/pallet
40 x 3 mm : 4 x roll 5X 30M/box - 120 pieces/pallet

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply