



## CHARACTERISTICS

- Highly resistant to aging
- One-sided self-adhesive
- Compatible with silicone, thiokol or other jointing compounds
- Resistant to salt water, chemicals, soap and detergents
- Closed cells
- Plasticizer-free

## APPLICATIONS

- Suitable for aluminium, PVC and wood frames

## TECHNICAL CHARACTERISTICS

|  |   |
|--|---|
| Full final strength (hours)                                      | 0.033   |
| Compression strength: DIN 53577                                  | 30%: 0,05 N/mm <sup>2</sup> 50%: 0,12 N/mm <sup>2</sup> 70%: 0,25 N/mm <sup>2</sup> |
| Water vapour permeability at 2 mm thickness: DIN 53122 (per 24h) | 1.8 g/m <sup>2</sup>  |
| Water absorption   | Na 7 dagen: 0,7%, na 28 dagen: 0,8% (DIN 53428)                                     |
| Temperature resistance   | -80°C - +100°C  |
| Shelf life of unopened product                                   | 12 months   |

## PACKING AND COLOURS

|  |
|--|
| Grey   |
| 9 x 2 mm : 26 x roll 5X 20M/box - 650 pieces/pallet  |
| 9 x 3 mm : 20 x roll 5X 20M/box - 500 pieces/pallet  |
| 9 x 4 mm : 16 x roll 5X 20M/box - 400 pieces/pallet  |
| 9 x 5 mm : 22 x roll 5X 10M/box - 550 pieces/pallet  |
| 15 x 2 mm : 12 x roll 5X 20M/box - 600 pieces/pallet |
| 15 x 3 mm : 12 x roll 5X 20M/box - 300 pieces/pallet |
| 20 x 3 mm : 8 x roll 5X 30M/box - 400 pieces/pallet  |
| 30 x 5 mm : 32 x roll 10M/box - 800 pieces/pallet    |
| 40 x 3 mm : 4 x roll 5X 30M/box - 120 pieces/pallet  |

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply