

**CHARACTERISTICS**

- colorless
- Lubricant
- Based on a high-quality translucent silicone
- Contains no metal particles

**APPLICATIONS**

- Anti-corrosion for different materials.
- Damp-resistance
- Glow on plastic and vinyl.
- Preventing rubbers to dry out.

**TECHNICAL CHARACTERISTICS**

Density (g/ml)	0.76
Application temperature	-40°C - +240°C
Dry matter content	20%
Self-ignition temperature	< 0°C
Shelf life of unopened product	12 months
Storage conditions	Store in a dry, cool place at +5°C to +25°C. Keep out of direct sunlight.

**PACKING AND COLOURS**

6 x spray can 600ML/box - 522 pieces/pallet

**METHOD OF USE****Preparation**

- The surfaces must be solid, dry and free of dust and grease.
- Shake vigorously before use.

**Application**

- Spray by briefly pressing the button on the connections to be protected. Allow to penetrate by maneuvering the lubricated parts.

**SAFETY**

Consult the safety information on the packaging and the safety data sheet for more information.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply