Technical data sheet

SILICONE SPRAY



CHARACTERISTICS

- colorless
- Lubricant
- Based on a high-quality translucent silicone
- Contains no metal particles

APPLICATIONS

- Anti-corrosion for different materials.
- Damp-resistance
- Glow on plastic and vinyl.
- Preventing rubbers to dry out.

TECHNICAL CHARACTERISTICS	
Density (g/ml)	0.62
Dry matter content	20%
Shelf life of unopened product	36 months
Storage conditions	Store in a dry, cool place at +5°C to +25°C. Keep out of direct sunlight.

PACKING AND COLOURS
6 x spray can 600ML/box - 522 pieces/pallet

METHOD OF USE

Preparation

- The surfaces must be solid, dry and free of dust and grease.
- Shake vigorously before use.

Application

- Spray by briefly pressing the button on the connections to be protected. Allow to penetrate by maneuvering the lubricated parts.

SAFETY

Consult the safety information on the packaging and the safety data sheet for more information.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply

DL CHEMICALS Since 1936 Manufacturer of Sealants

DL Chemicals nv
Roterijstraat 201-203 - Zone 5 Snepbeek - 8793 Waregem - Belgium
T +32 56 62 70 51 - F +32 56 60 95 68
info@dl-chem.com - **www.dl-chem.com**

Last Update: 24-11-2026