



CHARACTERISTICS

- Cleaning agent
- Solvent-based
- Ensures perfect adhesion of neutral silicones on painted metals.

APPLICATIONS

- For removing dirt and grease on non-lacquered and lacquered metals
- Can be used to remove the following dirt: asphalt marks, grease marks and all persistent dirt
- Must be used when subsequent sealing with neutral silicones is required.

TECHNICAL CHARACTERISTICS

Density (g/ml)	0.86
Consistency	Liquid
Smell	Characteristic
Shelf life of unopened product	12 months
Storage conditions	Store in a dry, cool place at +5°C to +25°C. Keep out of direct sunlight.

PACKING AND COLOURS

15 x bottle 500ML/box - 720 pieces/pallet

METHOD OF USE

Preparation

- It is recommended to carry out tests on every surface before use.

Application

- Clean the surface with a wet cloth.
- Wait until the surface is dry (depending the circumstances, it takes 5 minutes).
- Afterwards the sealant can be applied

SAFETY

Consult the safety information on the packaging and the safety data sheet for more information.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply