

# PERFECT JOINT TOOLING AGENT UNDILUTED



## CHARACTERISTICS

- Tooling agent
- This detergent has to be diluted with water at a ratio of 5 volumes of Perfect Joint Tooling Agent Undiluted in 95 volumes of water
- Leaves no traces after rinsing
- Completely pH-neutral
- Does not contain solvents or acids
- Does not affect the surface.

## APPLICATIONS

- To smooth the surface of fresh applied sealants such as silicone, polymer and polyurethane

## TECHNICAL CHARACTERISTICS

Density (g/ml)	1.065
pH	ca. 7.5
Shelf life of unopened product	12 months
Storage conditions	Store in a dry, cool place at +5°C to +25°C. Keep out of direct sunlight.

## PACKING AND COLOURS

**15 x bottle 500ML/box - 720 pieces/pallet**

**bottle 5l - 120 pieces/pallet**

## METHOD OF USE

### Application

- To smooth the surface of fresh applied sealants such as silicone, polymer and polyurethane
- To be applied to the surface and tooled with a smoothing tool

## SAFETY

Consult the safety information on the packaging and the safety data sheet for more information.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply