# **PERFECT JOINT TOOLING AGENT**



# CHARACTERISTICS

- Ready to use tooling agent
- Ready made solution: the product has already been brought to concentration and can be sprayed directly on the surface without diluting
- Completely pH-neutral
- Non agressive to the joint
- Does not leave stains after rinsing with water
- Does not contain solvents or acids
- Does not affect the surface

#### **APPLICATIONS**

 To smooth the surface of fresh applied sealants such as silicone, polymer and polyurethane

TECHNICAL CHARACTERISTICS	
рН	ca. 7.5
Shelf life of unopened product	12 months
Storage conditions	Store in a dry, cool place at $+5^{\circ}$ C to $+25^{\circ}$ C. Keep out of direct sunlight.

# PACKING AND COLOURS

12 x spray bottle 500ML/box - 480 pieces/pallet

# **METHOD OF USE**

### Application

- Spray the tooling agent directly on the joint.
- Wet the finger or a smoothing tool with the product and smooth the joint.

# SAFETY

Consult the safety information on the packaging and the safety data sheet for more information.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply

