

**CHARACTERISTICS**

- Single-sided, self-adhesive polyethylene strip
- Reinforced with wire
- Closed cells
- Highly resistant to ageing
- Free of softener
- Can be combined with silicon, Thiokol or other sealants
- Resistant to salt water, chemicals, soap and cleaning products

APPLICATIONS

- Suitable for aluminium, PVC and wood frames

TECHNICAL CHARACTERISTICS

Density: DIN 53420 (g/cm ³)	0.033
Compression strength: DIN 53577	30%: 0,05 N/mm ² 50%: 0,12 N/mm ² 70%: 0,25 N/mm ²
Water vapour permeability at 2 mm thickness: DIN 53122 (per 24h)	1.8 g/m ²
Water absorption	Na 7 dagen: 0,7%, na 28 dagen: 0,8% (DIN 53428)
Temperature resistance	-80°C - +100°C
Shelf life of unopened product	12 months

PACKING AND COLOURS

Grey
9 x 2 mm : 26 x roll 100M/box - 650 pieces/pallet
9 x 3 mm : 20 x roll 100M/box - 500 pieces/pallet
9 x 4 mm : 16 x roll 100M/box - 400 pieces/pallet
9 x 5 mm : 22 x roll 50M/box - 550 pieces/pallet
15 x 3 mm : 12 x roll 100M/box - 300 pieces/pallet
20 x 3 mm : 68 x roll 30M/box - 1700 pieces/pallet
30 x 5 mm : 40 x roll 10M/box - 1000 pieces/pallet
40 x 3 mm : roll 30m - 374 pieces/pallet

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply