PARASILICO CLEANER



CHARACTERISTICS

- Cleaning agent
- Degreaser
- Transparent liquid
- Does not contain antistatikum

APPLICATIONS

- Suitable for removing non-cured sealant
- As well as cleaning and degreasing of several surfaces
- Remark: On lacquered and anodized aluminium: before use, preliminary tests are necessary
- Essential part of the Parabond Panel System to achieve durable adhesion of the façade panel adhesive Parabond Panel on aluminium supporting structures and HPL façade panels.

TECHNICAL CHARACTERISTICS	
Density (g/ml)	0.72
Consistency	Liquid
Smell	Characteristic
Cooking interval	78 - 113°C
Flash point (CC, degrees C)	9
Self-ignition temperature	> 200°C
Shelf life of unopened product	24 months
Storage conditions	Store in a dry, cool place at +5°C to +25°C. Keep out of direct sunlight.

PACKING AND COLOURS
12 x spray can 400ML/box - 720 pieces/pallet
bottle 5I - 120 pieces/pallet
bottle 25I - 26 pieces/pallet

METHOD OF USE

Preparation

- The user needs to make sure that the product is suitable for the application. Consult our technical service if necessary.
- It is recommended to carry out tests on every surface before use.
- Shake vigorously before use.
- To remove uncured sealant, remove as much silicone as possible in advance with a rag or paper wad.

Application

Removing of fresh, non cured sealant: Remove as much as possible beforehand with a cloth or cleaning paper. Follow instructions below: Aerosol 400 ml:

- Spray from a distance on the surface or on the non cured sealant
- Then rub the surface with a clean cloth

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply



info@dl-chem.com - www.dl-chem.com

Last Update: 23-10-2025

Jerry can 5 I - 25 I

- Soak a cloth with Parasilico Cleaner and remove the remaining sealant
- Then rub the surface with a clean cloth

Cleaning and degreasing of surfaces Aerosol 400 ml:

- Spray from a distance on the surface
- Rub the surface in order to clean with a clean cloth or paper
- Renew the cleaning paper regularly

SAFETY

Consult the safety information on the packaging and the safety data sheet for more information.

TECHNICAL APPROVALS AND QUALITY LABELS

Tested by SHR according to BRL4101-7 and included in KOMO certificate no. 21184/25 for façade panel bonding.



This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply



info@dl-chem.com - www.dl-chem.com

Last Update: 23-10-2025