

**CHARACTERISTICS**

- Water-based primer
- Highly improved adherence
- In order to obtain an ideal adherence of the parquet adhesive and dispersion adhesive for flexible floor coverings
- Also reinforces floor surfaces on a concrete base
- Easy to use
- Fast drying
- Solvent free (odour free)

APPLICATIONS

- Bonding of ABS.
- Not suitable as a moisture barrier.
- Suitable as an adhesion primer for underfloor heating, when screed is dry
- Can be used on absorbent substrates and tiled floors.

TECHNICAL CHARACTERISTICS

Type of product	Acrylic dispersion
Density (g/ml)	1.02
Drying time (depending on the layer thickness and atmospheric conditions)	2 - 24 hours
Application temperature	+15°C - +25°C
Curing system	Physical drying
Shelf life of unopened product	12 months
Storage conditions	Store in a dry, cool place at +15°C to +25°C.

PACKING AND COLOURS

bottle 5l - 120 pieces/pallet

METHOD OF USE**Preparation**

- The surfaces must be solid, dry and free of dust and grease.
- Shake vigorously before use.

Application

- Shake the product before use.
- Apply the primer in one layer with a roll or a brush.
- The primer must be completely dry before you apply the parquet adhesive. Dry time is between 2 h and 24 h, depending on the circumstances. The primer cures by evaporation of water.

Consumption

100 - 200 ml/m² (5 - 10 m²/liter)

Cleaning

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply

- Before curing: Tools, surfaces and uncured residues can be removed with water.

SAFETY

Consult the safety information on the packaging and the safety data sheet for more information.

POINTS OF ATTENTION

- Not suitable for application outside.
- Do not apply to surfaces that are not protected against any rising moisture.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply