

**CHARACTERISTICS**

- Very easy to apply
- Solvent free
- Fast-drying
- Low odour
- Water-based primer
- Also strengthens cementitious screeds (screed)

**APPLICATIONS**

- Can be used on absorbent substrates and tiled floors.
- Suitable as an adhesion primer for optimal bonding of parquet adhesive and dispersion adhesive for flexible floors.

**TECHNICAL CHARACTERISTICS**

Type of product	Acrylic dispersion
Density (g/ml)	1.02
Drying time (depending on the layer thickness and atmospheric conditions)	2 - 24 hours
Application temperature	+15°C - +25°C
Curing system	Physical drying
Shelf life of unopened product	12 months
Storage conditions	Store in a dry, cool place at +15°C to +25°C.

**PACKING AND COLOURS**

**bottle 5l - 120 pieces/pallet**

**METHOD OF USE****Preparation**

- The surfaces must be solid, dry and free of dust and grease.
- Shake vigorously before use.

**Application**

- Shake the product before use.
- Apply the primer in one layer with a roll or a brush.
- The primer must be completely dry before you apply the parquet adhesive. Dry time is between 2 h and 24 h, depending on the circumstances. The primer cures by evaporation of water.

**Consumption**

100 - 200 ml/m<sup>2</sup> (5 - 10 m<sup>2</sup>/liter)

**Cleaning**

- Before curing: Tools, surfaces and uncured residues can be removed with water.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply

## SAFETY

Consult the safety information on the packaging and the safety data sheet for more information.

## POINTS OF ATTENTION

- Not suitable for application outside.
- Do not apply to surfaces that are not protected against any rising moisture.
- Not suitable as a moisture barrier against rising damp. In this case use Hydroblocker 3K.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply