



## CHARACTERISTICS

- Protective hydrophobic liquid
- Forms a water-resistant layer but maintains water vapor permeability
- The appearance of the substrate is preserved
- Deep and rapid penetration into the substrate
- Low odour
- Contains solvents

## APPLICATIONS

- Ideal for use on large, uninterrupted surfaces.
- Protect against heavy rain, frost damage, and green algae.
- Waterproofing of facade and bricks, concrete, plaster, porous roofing, and porous mineral substrates.
- Suitable for use on both existing and new buildings.
- Suitable for use on natural and artificial stone types such as sandstone, plaster, clay, cement, roof tiles, bricks...

## TECHNICAL CHARACTERISTICS

Type of product	Silyl-siloxane
Density (g/ml)	0.8
Consistency	Liquid
Application temperature	+10°C - +30°C
Dry matter content	9%
Flash point (CC, degrees C)	63
Shelf life of unopened product	12 months
Storage conditions	Transport and store upright in a dry, cool place at +5°C to +25°C.

## PACKING AND COLOURS

**2 x bottle 5L/box - 120 pieces/pallet**

Transparent

**bottle 25l - 26 pieces/pallet**

Transparent

## METHOD OF USE

### Preparation

- Cover the adjacent surfaces with paper, plastic wrap or other suitable material.
- The surface should be clean, dry to slightly moist. The surface must first be cleaned with water under pressure, by sand blasting or chemical treatment.
- Use suitable mortar to repair damaged surface. Cracks or tears wider than 0.15 mm must be filled.
- Clean the surface with Green Cleaner and let it dry

### Application

- Apply in one layer.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply

- Apply with a brush or roller.
- Apply with a low-pressure gun.
- Apply with a sprayer.
- Start the treatment at the top in a 40 cm strip with a back-and-forth motion. Always allow it to flow in a liquid curtain over the surface, saturating the entire area.

### Consumption

1 - 1.5 l/m<sup>2</sup>

### Cleaning

- Clean tools with white spirit.

### SAFETY

Consult the safety information on the packaging and the safety data sheet for more information.

### POINTS OF ATTENTION

- Do not apply in direct sun.
- Not suitable for synthetic crepi because absorption of the product is not possible and the water repellent will therefore have no effect. With mineral crepi, absorption does occur and the water repellent can be applied.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply