



## CHARACTERISTICS

- Water-based
- High end strength
- Low odour
- Assembly adhesive with very high final strength
- Mounting without nails or screws
- Small elements and moldings (including polystyrene)
- Solvent free

## APPLICATIONS

- Assembling and sealing elements in polystyrene or expanded polyurethane.
- Also suitable for bonding to concrete, masonry, plaster, wood, metal, PVC...

## TECHNICAL CHARACTERISTICS

Type of product	Synthetic elastomer emulsion in water
Density (g/ml)	1.65
Consistency	Pasta
Temperature resistance	-25°C - +70°C
Working time at 23 degrees C and 50% R.H.	13 - 18 minutes
VOC	< 50 g/l
Tensile strength wood/wood at 20 degrees C (kg/cm <sup>2</sup> )	45
Shelf life of unopened product	15 months
Storage conditions	Store in a dry, cool place at +5°C to +25°C. Keep out of direct sunlight.

## PACKING AND COLOURS

12 x cartridge 290ML/box - 1200 pieces/pallet  
White

## METHOD OF USE

### Preparation

- The surfaces must be solid, dry and free of dust and grease.
- The surface must be solid, strong enough and clean, dust and fat-free.
- Degrease the materials to be glued with Multi-Purpose Super Cleaner, MEK, fire alcohol, ethanol if necessary.

### Cleaning

- Before curing: Tools, surfaces and uncured residues can be removed with water.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply

## SAFETY

Consult the safety information on the packaging and the safety data sheet for more information.

## TECHNICAL APPROVALS AND QUALITY LABELS

- French VOC emission class A+



This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply