# **PARAROOF COLD GLUE**



#### **CHARACTERISTICS**

- · Flexible bituminous cold glue
- Reinforced by fibers
- Levels minor irregularities

#### **APPLICATIONS**

• Bonding bituminous sealing layer without fire hazard on various surfaces such as bituminous roofing, concrete, insulation, metal, etc.

| TECHNICAL CHARACTERISTICS      |  |
|--------------------------------|--|
| Type of product                | Bitumen with fibre reinforcement, additives and solvents           |
| Density (g/ml)                 | 1.15   |
| Consistency                    | Liquid pasta   |
| Viscosity                      | 31.000 - 46.000 mPa.s (Haake 25°C)                                 |
| Curing time                    | 24 hours   |
| Application temperature        | +5°C - +35°C   |
| Dry matter content             | ±80%   |
| Shelf life of unopened product | 36 months  |
| Storage conditions             | Transport and store upright in a dry, cool place at +5°C to +25°C. |

# PACKING AND COLOURS can 5kg - 120 pieces/pallet Black

# **METHOD OF USE**

#### **Preparation**

- The surfaces must be solid, dry and free of dust and grease.
- Stir the product well.

# **Primers**

• On a very absorbent or very dusty surface (concrete, cement, etc.) first apply a coat of Pararoof Quick Primer (drying time 30 min).

#### **Application**

Apply in one layer.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply



info@dl-chem.com - www.dl-chem.com

Last Update: 19-10-2025

- Unroll the roofing rolls and press them into the adhesive, with 8 cm overlaps without adhesive. For detailed finishing, upstanding edges, and overlaps, bond with Pararoof Super and seal with Pararoof Super or Pararoof Bitumen.
- Apply with a floor squeegee or brush.
- Apply weight to the edges of the glued roof rolls during drying and up to one month after application for maximum results.

# Consumption

 $1 - 1.5 \text{ kg/m}^2$  depending on the porosity of the substrate.

## Cleaning

Clean tools with white spirit.

# **SAFETY**

Consult the safety information on the packaging and the safety data sheet for more information.

# **POINTS OF ATTENTION**

• The use of Pararoof Cold Glue is limited to a slope of <15% of the flat roof.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply



info@dl-chem.com - www.dl-chem.com

Last Update: 19-10-2025