



CHARACTERISTICS

- Excellent adhesion to almost all building materials
- High resistance to UV
- Excellent flexibility
- High resistance to ageing and weather conditions
- Excellent humidity resistance
- Reinforced by fibers
- Can be used (cold) immediately after unwrapping
- Tixothrope: cannot drip, flow or spill and makes no threads
- Free from asbestos

APPLICATIONS

- Repair of gutters and downspouts.
- Waterproof finishing of complex roof details such as domes, upstands, skylights, chimneys, ventilation pipes, gutters, etc.
- Sealing of bituminous surfaces, roofing, roof rolls, tiles, insulation boards, etc
- Waterproof sealing of joints, seams, and roof edge closures

TECHNICAL CHARACTERISTICS

Type of product	Bitumen, rubber, resin, polymers, fibres
Density (g/ml)	1.33
Consistency	Pasta
Application temperature	+5°C - +30°C
Temperature resistance	-20°C - +80°C
Curing system	Physical drying
Consistence: ISO 7390	Non-existent
Shelf life of unopened product	36 months
Storage conditions	Store in a dry, cool place at +5°C to +25°C. Keep out of direct sunlight.

PACKING AND COLOURS

12 x cartridge 300ML/box - 1200 pieces/pallet
Black

METHOD OF USE

Preparation

- The surfaces must be solid, dry and free of dust and grease.
- The user needs to make sure that the product is suitable for the application. Consult our technical service if necessary.
- It is recommended to carry out tests on every surface before use.
- Test the product's compatibility with polystyrene and other insulation boards.

Primers

- On a very absorbent or very dusty surface (concrete, cement, etc.) first apply a coat of Pararroof Quick Primer (drying time 30 min).

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply

Application

- Apply using a manual caulking gun or putty knife.
- Do not subject the joint to thermal, mechanical or chemical stress before curing is complete.

Cleaning

- Clean tools with white spirit
- After curing remove mechanically.

SAFETY

Consult the safety information on the packaging and the safety data sheet for more information.

POINTS OF ATTENTION

- Not suitable for use on natural stone (can cause stains).
- Not suitable for use on EPDM.
- Do not use on plastics.
- Contact with mineral oils softens the product.
- Not suitable for use on insulation boards that are not resistant to solvents
- Not suitable for use on plastic materials containing plasticizers.
- Test the product's compatibility with polystyrene and other insulation boards.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply