



CHARACTERISTICS

- Tixotrope: cannot drip, flow or spill and makes no threads
- Protective hydrophobic gel
- Forms a water-resistant layer but maintains water vapor permeability
- The appearance of the substrate is preserved
- Deep and rapid penetration into the substrate

APPLICATIONS

- Ideal for use on small surfaces.
- Protect against heavy rain, frost damage, and green algae.
- Waterproofing of facade and bricks, concrete, plaster, porous roofing, and porous mineral substrates.
- Suitable for use on both existing and new buildings.
- Suitable for use on natural and artificial stone types such as sandstone, plaster, clay, cement, roof tiles, bricks...

TECHNICAL CHARACTERISTICS

| | |
|--------------------------------|--|
| Type of product | Silyl-siloxane |
| Density (g/ml) | 0.848 |
| % active substance | 25 |
| Consistency | Gel |
| Application temperature | +10°C - +30°C |
| Flash point (CC, degrees C) | 65 |
| Shelf life of unopened product | 15 months |
| Storage conditions | Transport and store upright in a dry, cool place at +5°C to +25°C. |

PACKING AND COLOURS

bucket 5l - 60 pieces/pallet
White

METHOD OF USE

Preparation

- The surfaces must be solid, dry and free of dust and grease.
- Cover the adjacent surfaces with paper, plastic wrap or other suitable material.
- Use suitable mortar to repair damaged surface. Cracks or tears wider than 0.15 mm must be filled.
- Clean the surface with Green Cleaner and let it dry

Application

- Apply in one layer.
- Apply with a brush or roller.
- Apply with a low-pressure gun.

Consumption

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply

100 - 200 g/m² (depending on the surface's absorption).

Cleaning

- Clean tools with white spirit.

SAFETY

Consult the safety information on the packaging and the safety data sheet for more information.

POINTS OF ATTENTION

- Do not apply in direct sun.
- Not suitable for synthetic crepi because absorption of the product is not possible and the water repellent will therefore have no effect. With mineral crepi, absorption does occur and the water repellent can be applied.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply