



## CHARACTERISTICS

- Very easy to apply
- Can be applied to dry and slightly damp surfaces
- Protective hydrophobic liquid
- Suitable for porous mineral substrates such as cement, concrete, masonry...
- Forms a vapor barrier and water-repellent layer

## APPLICATIONS

- Suitable for use in the most demanding locations.
- Protect foundations, submerged structures and steel beams from groundwater.
- Suitable for outdoor use.

## TECHNICAL CHARACTERISTICS

Type of product	Bitumen and solvents
Density (g/ml)	0.89
Consistency	Liquid
Viscosity	80 - 155 mm <sup>2</sup> /s (Ubbelohde)
Drying time (depending on the layer thickness and atmospheric conditions)	24 hours
Application temperature	0°C - +35°C
Dry matter content	±50%
Shelf life of unopened product	36 months
Storage conditions	Transport and store upright in a dry, cool place at +5°C to +25°C.

## PACKING AND COLOURS

**barrel 25l - 22 pieces/pallet**

Black

**can 5l - 120 pieces/pallet**

Black

## METHOD OF USE

### Preparation

- The surface must be solid, strong enough and clean, dust and fat-free.
- Remove any water, water film or raindrops. The best adhesion is obtained on a dry surface.
- Stir the product well.
- Fill voids and imperfections with cement mortar to achieve a smooth and even finish.

### Application

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply

- Apply in 2 coats for maximum protection. Apply the second coat only after complete drying of the first coat (after  $\pm 24$  hours, depending on temperature and weather conditions).
- Apply with a brush.

### Consumption

First layer of 0.67 l/m<sup>2</sup> and a second layer of 0.4 l/m<sup>2</sup>, except for metal where 0.4 l/m<sup>2</sup> per layer must be applied.

### Cleaning

- Clean tools with white spirit.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply