



CHARACTERISTICS

- One component glue
- Very high traction adhesive: no nails or screws needed
- Gap filling: possible to bond materials to uneven surfaces (up to 8 mm)
- Horizontal and vertical

APPLICATIONS

- Gluing of wooden & plastic laths, ornaments, frames, doorsteps, window sills, skirting boards, roofing elements...
- For both absorbent and non-absorbent surfaces.
- Indoor and outdoor use.

TECHNICAL CHARACTERISTICS

| | |
|--|---|
| Density (g/ml) | 1.22 |
| Consistency | Pasta |
| Curing time | 48 hours |
| Application temperature | +10°C - +40°C |
| Temperature resistance | -20°C - +100°C |
| Dry matter content | 60% |
| Tensile strength wood/wood at 20 degrees C (kg/cm ²) | 60 |
| Shelf life of unopened product | 12 months |
| Storage conditions | Store in a dry, cool place at +5°C to +25°C. Keep out of direct sunlight. |

PACKING AND COLOURS

25 x cartridge 310ML/box - 1200 pieces/pallet

Beige

METHOD OF USE

Preparation

- The surfaces must be solid, dry and free of dust and grease.
- If needed degrease the materials to be glued with Parasilico Cleaner, MEK, fire alcohol, ethanol.
- The user needs to make sure that the product is suitable for the application. Consult our technical service if necessary.

Application

- Apply the product from the cartridge or foil packaging with a manual or pneumatic caulking gun.
- Apply in cords of min. 5 mm diameter and with a max. of 10 cm between the parallel lines.
- Press on the other surface, take off, wait a few minutes to let the vapours escape. Apply again and press hard (Transfer method).

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply

- The object has to be positioned with great precision, as the setting is almost immediate.
- Where heavier items are being fixed, support them while the adhesive is drying to eliminate any possible slippage.

Consumption

- 1 cordon of 5 mm width covers approx. 15 meters per cartridge
- Baseboards < 7 cm in width: 1 line of glue
- Baseboards > 7 cm in width: 2 lines of glue.

Cleaning

- With toluene.

SAFETY

Consult the safety information on the packaging and the safety data sheet for more information.

POINTS OF ATTENTION

- Not suitable for permanent submersion.
- Do not use on plastics.
- Not appropriate for use on polystyrene (XPS, EPS).

TECHNICAL APPROVALS AND QUALITY LABELS

- French VOC emission class A+



This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply