

**CHARACTERISTICS**

- Light finishing paste
- Ready-to-use
- No wrinkles or cracks
- Paintable after a few minutes, ideally after ± 2 hours
- Can be applied in one single movement
- Can be abraded
- Solvent and phthalate free
- Shrink-free
- Fast-drying
- Suitable for porous surfaces (wood such as MDF and OSB, masonry, stone, concrete, plaster...)

APPLICATIONS

- Filling of cracks, static joints, gaps and screw holes of max. 50 mm deep and 50 mm wide.
- Suitable for indoor use only.

TECHNICAL CHARACTERISTICS

Type of product	Acrylic dispersion
Density (g/ml)	0.45
Consistency	Pasta
Application temperature	+5°C - +35°C
Temperature resistance	-20°C - +80°C
Shrinkage: ISO 10563	Non-existent
Sandable after	24 h
Working time at 23 degrees C and 50% R.H.	10 - 15 minutes
Shelf life of unopened product	15 months
Storage conditions	Store in a dry, cool place at +5°C to +25°C. Keep out of direct sunlight.

PACKING AND COLOURS**25 x cartridge 310ML/box - 1200 pieces/pallet**

White

bucket 5l - 60 pieces/pallet

White

6 x bucket 1l/box - 384 pieces/pallet

White

bucket 10l - 33 pieces/pallet

White

METHOD OF USE**Preparation**

- The surfaces must be solid, dry and free of dust and grease.
- If needed degrease the materials to be glued with Parasilico Cleaner, MEK, fire alcohol, ethanol.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply

- Bucket: Stir before use. When too dry, add one coffee spoon of water for each 250 ml of product and stir until a smooth paste is obtained.

Application

- Apply the product from the cartridge or foil packaging with a manual or pneumatic caulking gun.

Tooling

- With a wet putty knife.

Cleaning

- Before curing: Tools, surfaces and uncured residues can be removed with water.

Repairing

It is recommended to use the same product.

Paintable

- Given the wide variety of paint types available, it is recommended to test the compatibility of the sealant/adhesive with the paint in advance.
- Has to be painted twice when used outdoors.

SAFETY

Consult the safety information on the packaging and the safety data sheet for more information.

POINTS OF ATTENTION

- Not suitable for permanent submersion.
- Not suitable for use on butiminous surfaces.
- Not suitable for use on PE, PP, PA, PTFE (Teflon).
- Cannot be used on synthetic, metal surfaces.
- Not suitable for glazing joints.
- The sealant cures by water evaporation. At low temperatures and high humidity, evaporation and curing are slower.
- Not suitable for application outside.
- Not suitable for expansion joints.
- To prevent leaching, avoid contact with water (rain or other) within 2 hours of sealant application.
- Not suitable for use on glass.
- Not suitable for filling holes in wood (no filling paste).

TECHNICAL APPROVALS AND QUALITY LABELS

- French VOC emission class A+



This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply