

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form : Mixture
Trade name : Parabond Marine Parquet

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Main use category : Professional use

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

DL CHEMICALS
Roterijstraat 201-203
B-8793 Waregem - Belgium
T + 32 56 62 70 51 - F + 32 56 60 95 68
info@dl-chem.com - www.dl-chem.com

1.4. Emergency telephone number

Emergency number : + 32 70 245 245

Country	Official advisory body	Address	Emergency number	Comment
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	+44 20 7188 7188	

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture**

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids Not classified

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH208 - Contains Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate, 3-aminopropyltriethoxysilane, 3-(2-aminoethylamino)propyltrimethoxysilane. May produce an allergic reaction.
EUH210 - Safety data sheet available on request.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients**3.1. Substances**

Not applicable

Parabond Marine Parquet

Safety Data Sheet

according to Regulation (EU) 2015/830

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
vinyltrimethoxysilane	(CAS-No.) 2768-02-7 (EC-No.) 220-449-8 (REACH-no) 01-2119513215-52	2,5 - 5	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Move to fresh air.
First-aid measures after skin contact : Wash with plenty of water/....
First-aid measures after eye contact : Wash with plenty of water/.... If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion : Rinse mouth out with water.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Not expected to present a significant inhalation hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact : Not expected to present a significant skin hazard under anticipated conditions of normal use.
Symptoms/effects after eye contact : May cause slight irritation.
Symptoms/effects after ingestion : Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : All extinguishing media allowed.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Not combustible. Not flammable.

5.3. Advice for firefighters

Protection during firefighting : Wear suitable protective clothing. Wear a self contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Wear respiratory protection.

6.2. Environmental precautions

Do not allow into drains or water courses.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with eyes.
Handling temperature : 5 - 40 °C

Parabond Marine Parquet

Safety Data Sheet

according to Regulation (EU) 2015/830

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in dry, well-ventilated area.
Maximum storage period : 12 months
Storage temperature : 5 - 25 °C

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protective equipment:

Gloves. Safety glasses.

Hand protection:

Time of penetration is to be checked with the glove producer. Please follow the instructions related to the permeability and the penetration time provided by the manufacturer. Gloves must be replaced after each use and whenever signs of wear or perforation appear

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	> 0,1		EN 374

Eye protection:

Type	Use	Characteristics	Standard
Safety glasses		With side shields	EN 166

Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use

Respiratory protection:

No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation



Environmental exposure controls:

Do not allow to enter into surface water or drains.

Consumer exposure controls:

Avoid contact with skin and eyes.

Other information:

Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Paste.
Colour : According to product specification.
Odour : characteristic.
Density : 1,4 g/cm³ at 20 °C

Parabond Marine Parquet

Safety Data Sheet

according to Regulation (EU) 2015/830

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

None under normal conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

vinyltrimethoxysilane (2768-02-7)	
LD50 oral rat	7120 mg/kg
LD50 dermal rabbit	3540 mg/kg
LC50 inhalation rat (mg/l)	16,79 mg/l/4h
LC50 inhalation rat (ppm)	2773 ppm/4h (OECD 403 method)
LC50 inhalation rat (Dust/Mist - mg/l/4h)	16,8 mg/l/4h

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

vinyltrimethoxysilane (2768-02-7)	
LOAEL (oral, rat, 90 days)	10 - 100 mg/kg bodyweight/day

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Acute aquatic toxicity : Not classified

Chronic aquatic toxicity : Not classified

vinyltrimethoxysilane (2768-02-7)	
LC50 fish 1	191 mg/l
EC50 Daphnia 1	168,7 mg/l
EC50 72h algae (1)	> 957 mg/l
ErC50 (algae)	> 100 mg/l (OECD 201 method)
NOEC chronic fish	>= 100 mg/l
NOEC chronic crustacea	28 mg/l

Parabond Marine Parquet

Safety Data Sheet

according to Regulation (EU) 2015/830

vinyltrimethoxysilane (2768-02-7)	
NOEC chronic algae	957 mg/l

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.

SECTION 14: Transport information

In accordance with ADR

ADR

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Dangerous for the environment : No

No supplementary information available

14.6. Special precautions for user

- Overland transport

No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Flam. Liq. 3	Flammable liquids, Category 3

Parabond Marine Parquet

Safety Data Sheet

according to Regulation (EU) 2015/830

Flam. Liq. Not classified	Flammable liquids Not classified
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
H226	Flammable liquid and vapour.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
EUH208	Contains Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate, 3-aminopropyltriethoxysilane, 3-(2-aminoethylamino)propyltrimethoxysilane. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

MSDS Reach Annex II DL-Chem

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product