

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Paraflex 40

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

DL CHEMICALS
Roterijstraat 201-203
B-8793 Waregem - Belgium
T + 32 56 62 70 51 - F + 32 56 60 95 68
info@dl-chem.com - www.dl-chem.com

1.4. Emergency telephone number

Country	Official advisory body	Address	Emergency number	Comment
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	+44 20 7188 7188	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH208 - Contains N-(2-aminoethyl)-N'-[3-(trimethoxysilyl)propyl]ethylenediamine, 3-(2-aminoethylamino)propyltrimethoxysilane, Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.
EUH210 - Safety data sheet available on request.

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Paraflex 40

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
calcium carbonate substance with national workplace exposure limit(s) (GB)	(CAS-No.) 471-34-1 (EC-No.) 207-439-9 (REACH-no) 01-2119486795-18	25 – 75	Not classified
Titanium dioxide substance with national workplace exposure limit(s) (GB)	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5 (REACH-no) 01-2119489379-17	1 – 5	Not classified
vinyltrimethoxysilane	(CAS-No.) 2768-02-7 (EC-No.) 220-449-8 (REACH-no) 01-2119513215-52	1 – 2,5	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation: vapour), H332
Silane, dichlorodimethyl-, reaction products with silica substance with national workplace exposure limit(s) (GB)	(CAS-No.) 68611-44-9 (EC-No.) 271-893-4 (REACH-no) 01-2119379499-16	1 – 2,5	Not classified

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Move to fresh air.
First-aid measures after skin contact	: Wash with plenty of water/...
First-aid measures after eye contact	: Immediately rinse with water for a prolonged period while holding the eyelids wide open.
First-aid measures after ingestion	: Rinse mouth.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Not expected to present a significant inhalation hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	: Not expected to present a significant skin hazard under anticipated conditions of normal use.
Symptoms/effects after eye contact	: May cause slight irritation.
Symptoms/effects after ingestion	: Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: All extinguishing media allowed. Use extinguishing media appropriate for surrounding fire.
------------------------------	--

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Not flammable.
-------------	------------------

5.3. Advice for firefighters

Precautionary measures fire	: Do not breathe fumes from fires or vapours from decomposition. Evacuate unnecessary personnel. Exercise caution when fighting any chemical fire.
Firefighting instructions	: Cool down the containers exposed to heat with a water spray.
Protection during firefighting	: Wear a self contained breathing apparatus.
Other information	: Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection. Equip rescue crew with proper protection.
----------------------	--

6.2. Environmental precautions

Do not allow into drains or water courses.

Paraflex 40

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.3. Methods and material for containment and cleaning up

For containment : Cover spill with non combustible material, e.g.: sand, earth, vermiculite.
 Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Warning! Avoid exposure.
 Handling temperature : 5 – 40 °C
 Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store tightly closed in a dry and cool place.
 Maximum storage period : 12 months
 Storage temperature : 5 – 25 °C

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

calcium carbonate (471-34-1)		
United Kingdom	WEL TWA (mg/m ³)	10 mg/m ³ inhalable dust 4 mg/m ³ respirable dust
Silane, dichlorodimethyl-, reaction products with silica (68611-44-9)		
United Kingdom	WEL TWA (mg/m ³)	6 mg/m ³
United Kingdom	WEL STEL (mg/m ³)	2,4 mg/m ³
Titanium dioxide (13463-67-7)		
United Kingdom	WEL TWA (mg/m ³)	10 mg/m ³ inhalable dust 4 mg/m ³ respirable dust

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Hand protection:

In case of repeated or prolonged contact wear gloves. Time of penetration is to be checked with the glove producer. Please follow the instructions related to the permeability and the penetration time provided by the manufacturer. Gloves must be replaced after each use and whenever signs of wear or perforation appear

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	3 (> 60 minutes)	> 0,35		EN ISO 374

Eye protection:

Type	Use	Characteristics	Standard
Safety glasses	Droplet	With side shields	EN 166

Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use

Respiratory protection:

No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation

Device	Filter type	Condition	Standard
Gas mask	ABEK	If conc. in air > exposure limit	

Paraflex 40

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830



Consumer exposure controls:

Avoid contact with skin and eyes. Do not eat, drink or smoke during work.

Other information:

Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Paste.
Colour	: According to product specification.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1,5 g/cm ³
Solubility	: Water: Insoluble
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

None under normal conditions.

10.2. Chemical stability

Stable at ambient temperature and under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

No additional information available

Paraflex 40

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.6. Hazardous decomposition products

Additional hazards when processed. release of (highly) toxic gases/vapours. Methanol.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

calcium carbonate (471-34-1)	
LD50 oral rat	> 2000 mg/kg (OECD 420 method)
LD50 dermal rat	> 2000 mg/kg (OECD 402 method)
LC50 inhalation rat (mg/l)	> 3 mg/l/4h (OECD 403 method)

Silane, dichlorodimethyl-, reaction products with silica (68611-44-9)	
LD50 oral rat	> 5000 mg/kg (OECD 423 method)
LD50 dermal rabbit	> 2000 mg/kg (OECD 402 method)
LC50 inhalation rat (mg/l)	> 0,477 mg/l/4h

vinyltrimethoxysilane (2768-02-7)	
LD50 oral rat	7120 mg/kg
LD50 dermal rabbit	3259 mg/kg
LC50 inhalation rat (ppm)	2773 ppm/4h
LC50 inhalation rat (Vapours - mg/l/4h)	16,8 mg/l/4h

Titanium dioxide (13463-67-7)	
LD50 oral rat	> 5000 mg/kg (OECD 425 method)
LD50 dermal rat	> 10000 mg/kg
LD50 dermal rabbit	> 10000 mg/kg
LC50 inhalation rat (mg/l)	> 6,82 mg/l
LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 6,82 mg/l/4h

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

vinyltrimethoxysilane (2768-02-7)	
NOAEL (oral, rat, 90 days)	200 mg/kg bodyweight/day

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

calcium carbonate (471-34-1)	
LC50 fish 1	> 100 mg/l OECD 203 method
EC50 Daphnia 1	> 100 mg/l (OECD 202 method)
EC50 other aquatic organisms 2	> 1000 mg/l (OECD 209 method)
EC50 72h algae (1)	> 14 mg/l OECD 201 method
EC50 72h algae (2)	> 100 mg/l OECD 201 method
ErC50 (algae)	> 1000 mg/l (OECD 201 method)

Paraflex 40

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

calcium carbonate (471-34-1)	
NOEC (acute)	14 mg/l (OECD 201 method)
Silane, dichlorodimethyl-, reaction products with silica (68611-44-9)	
LC50 fish 1	> 10000 mg/l (OECD 203 method)
EC50 Daphnia 1	> 10000 mg/l (OECD 202 method)
EC50 72h algae (1)	> 10000 mg/l
vinyltrimethoxysilane (2768-02-7)	
LC50 fish 1	191 mg/l
EC50 Daphnia 1	168,7 mg/l
EC50 72h algae (1)	> 210 mg/l
ErC50 (algae)	> 100 mg/l (OECD 201 method)
NOEC chronic algae	25 mg/l
Titanium dioxide (13463-67-7)	
LC50 fish 1	> 1000 mg/l pimephales promelas
LC50 fish 2	> 10000 mg/l
EC50 Daphnia 1	> 100 mg/l (OECD 202 method)
EC50 other aquatic organisms 1	> 1000 mg/l
EC50 other aquatic organisms 2	61 mg/l
EC50 72h algae (2)	> 100 mg/l pseudokirchneriella subcapitata
NOEC chronic algae	5600 mg/l

12.2. Persistence and degradability

Titanium dioxide (13463-67-7)	
Persistence and degradability	Not readily biodegradable.

12.3. Bioaccumulative potential

calcium carbonate (471-34-1)	
Bioaccumulative potential	Low bioaccumulation potential.

12.4. Mobility in soil

calcium carbonate (471-34-1)	
Ecology - soil	insoluble in water.

12.5. Results of PBT and vPvB assessment

Paraflex 40	
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII	
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
Component	
vinyltrimethoxysilane (2768-02-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Empty the packaging completely prior to disposal.
Product/Packaging disposal recommendations	: Dispose of contaminated materials in accordance with current regulations.
European List of Waste (LoW) code	: 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances

Paraflex 40

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 14: Transport information

In accordance with ADR

ADR
14.1. UN number
Not applicable
14.2. UN proper shipping name
Not applicable
14.3. Transport hazard class(es)
Not applicable
14.4. Packing group
Not applicable
14.5. Environmental hazards
Not applicable
No supplementary information available

14.6. Special precautions for user

- Overland transport
Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:	
3(a) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	vinyltrimethoxysilane ; methanol
40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	vinyltrimethoxysilane ; methanol
3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	vinyltrimethoxysilane ; methanol ; N-(2-aminoethyl)-N'-[3-(trimethoxysilyl)propyl]ethylenediamine ; 3-(2-aminoethylamino)propyltrimethoxysilane ; Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate ; Dioctyltinbis(acetylacetonate)
3(c) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	N-(2-aminoethyl)-N'-[3-(trimethoxysilyl)propyl]ethylenediamine ; 3-(2-aminoethylamino)propyltrimethoxysilane ; reaction mass of: isomers of 2-(2H-benzotriazol-2-yl)-4-methyl-(n)-dodecylphenol, isomers of 2-(2H-benzotriazol-2-yl)-4-methyl-(n)-tetracosylphenol, isomers of 2-(2H-benzotriazol-2-yl)-4-methyl-5,6-didodecylphenol. n = 5 or 6 ; Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate ; reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate
69. Methanol	methanol

Paraflex 40

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out

Silane, dichlorodimethyl-, reaction products with silica

SECTION 16: Other information

Full text of H- and EUH-statements:

Acute Tox. 4 (Inhalation: vapour)	Acute toxicity (inhalation: vapour) Category 4
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H332	Harmful if inhaled.
EUH208	Contains N-(2-aminoethyl)-N'-[3-(trimethoxysilyl)propyl]ethylenediamine, 3-(2-aminoethylamino)propyltrimethoxysilane, Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

MSDS Reach Annex II DL-Chem

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.